

IS6T

FEATURES

- Extremely compact enclosure
- Accurate sound reproduction
- Fast and secure mounting arrangement
- 100V transformers included (15/30 W or by-pass position)
- Available in black or white colours

APPLICATIONS

- Multimedia Facilities, Presentation Suites, Boardrooms
- Lecture Halls, Theme Venues
- Stores, Boutiques
- Music-restaurants, Dance & dinner clubs
- Show-rooms, Shopping malls
- Fitness & Wellness centres

DESCRIPTION

The IS6T is a high fidelity, full-range loudspeaker system mounted in a plastic sealed box and designed for background music distribution. IS6T features a 6.5" (16.5 cm) LF cone driver with a Neodymium HF section. The system employs an optimized passive crossover (1st order acoustic slopes) to integrate both the on-axis and off-axis characteristics of the HF and LF sections. A 100V transformer is integrated within the cabinet and a multitap switch for low impedance use enables the users to choose 15W, 30W or by-pass position.



TECHNICAL SPECIFICATIONS:

FREQUENCY RESPONSE

IS6T (±5 dB) 110 Hz ÷ 20 kHz

IMPEDANCE (Ω)

IS6T 8

MAX SENSITIVITY (dB SPL @ 1W 1m)

IS6T 90

POWER - WATT MAX

IS6T 100

MAX SPL @ 1 m (calculated)

IS6T 113 Peak

COMPONENTS AND LOADING

IS6T Low 6.5" cone driver
High 19 mm Neodymium transducer

ACCESSORIES INCLUDED

IS6T Bracket, 100V transformer (15/30W/ by-pass)

WEIGHT

	Single unit	Shipping (2 units)
WEIGHT	4.2 kg (9.3 lb)	9.5 kg (20.9 lb)

DIMENSIONS

Height	28 cm (11.0")	34 cm (13.4")
Width	19 cm (7.5")	24 cm (9.4")
Depth	17 cm (6.7")	41 cm (16.1")

INSTALLATION SERIES